

SPEC SHEET ABT-HC-26S

Product Name:	ABT-HC-26S
Features:	<ul style="list-style-type: none"> • Premier Solid Door Laboratory Refrigerator • 26 Cu. Ft. capacity • One swing solid door, self-closing, right hinged, not reversible • Microprocessor Temperature Controller • Adjustable operating temperature range: 1°-10°C • Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms • Sample simulated digital temperature display; .1° Resolution • Adjustable temperature display in Celsius or Fahrenheit • Audible and visual high/low temperature alarms • 2 probes; 1 in air and 1 in sample bottle • Sensor error alarm, Power failure alarm, Alarm mute with ring back • Resettable 1-point Min/Max History • Remote alarm contacts • Alarm validation (audible, visual, and remote alarm) • Four adjustable shelves (adjustable in ½" increments) • Forced draft air circulation • Keyed door lock, Magnetic door gasket for positive seal, Heavy duty door handle • LED interior lights are safety shielded and switch controlled • Swivel casters (3 ½"), probe access port (3/8") • White powder-coated steel exterior and interior • Hydrocarbon, natural refrigerant (R290) • Two year parts and labor warranty, plus an additional three compressor parts warranty • Exterior dimensions: 28 ¾" W x 36 ½" D x 81 ¾" H with casters; 78¼" H without casters • Cycle defrost • 115V, 60 Hz, 3 Amps, 1/5 HP • ETL listed • Shipping weight: 275 lbs.