

SPEC SHEET ABT-HC-CP-47-TS

Product Name:	ABT-HC-CP-47-TS
Features:	<ul style="list-style-type: none"> • Templog Premier Glass Door Chromatography Refrigerator • 47 Cu. Ft. capacity • Two sliding glass doors, self-closing (energy efficient, double pane vacuum insulated) • Microprocessor temperature controller • Adjustable operating temperature range: 1°C - 10°C • Touch Screen Digital Temperature Display and Alarm Module • Password-protected control panel • Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit • Active temperature scale bar display • Resettable 1-point min/max history • Digital 24-hour temperature chart • Temperature data logging • USB port for data transfer and software updates • Real-time operational display clock • 4-20mA output • Electronic troubleshooting guide • Electronic QR Code to access Owner's Manual & technical support contact info • Adjustable alarm volume • Audible and visual high/low temperature alarms • 2 probes; 1 in air and 1 in sample bottle • Sensor error alarm; power failure alarm, door ajar alarm, low battery alarm • Operation indicator

SPEC SHEET ABT-HC-CP-47-TS

Product Name:	ABT-HC-CP-47-TS
Features:	<ul style="list-style-type: none"> • Alarm validation (audible, visual, and remote alarm), Alarm mute with ring back, Remote alarm contacts • Eight adjustable shelves (adjustable in 1/2" increments) • Forced draft air circulation • Keyed door locks • One GFCI protected duplex electrical outlet • Two 2" access ports with spring-loaded, self-closing gasketed metal covers • Magnetic door gasket for positive seal and integrated door handles • LED interior lights are safety shielded and switch controlled • Swivel Casters (3 1/2") Probe access port (3/4") • Advanced hydrocarbon detector • White powder-coated steel exterior and interior • High density urethane foam cabinet insulation • Hydrocarbon, natural refrigerant (R290) • Three year parts and labor warranty, plus an additional two year compressor parts warranty • Exterior dimensions: 55 5/8" W x 33 1/4" D x 81 3/4" H with casters; 78 1/4" H without casters. *Width w/access ports closed; 63 5/8" width w/access ports open • Cycle defrost • 115V, 60 Hz, 4.5 Amps, 1/4 HP • ETL listed • Shipping weight: 508 lbs. • Note: This unit requires two (2) outlets