

SPEC SHEET ABT-HC-ERP-17

Product Name:	ABT-HC-ERP-17
Features:	<ul style="list-style-type: none"> • Standard Hazardous Location (Explosion Proof) Refrigerator • 17 Cu. Ft. Capacity • One solid swing door, right hinged, not reversible • Microprocessor Temperature Controller • Adjustable operating temperature range: 1°C – 10°C • 5 adjustable shelves • Keyed door lock • Magnetic door gasket for positive seal • Heavy duty door handle • Leveling legs • White textured cabinet and door • High density urethane foam cabinet and door insulation • Natural, Hydrocarbon Refrigerant (R600a) • Exterior dimensions: 30 3/4"W x 28 5/8"D x 67 3/4"H • Cycle defrost • Not equipped with line cord and plug; must be hardwired in conduit to 120 VAC power source • 115V, 60Hz, 3 Amps, 1/4 HP • ETL listed • Two year parts and labor warranty • Meet NFPA and OSHA guidelines for hazardous locations, Class 1, Division II, Group C & D. These units are engineered for use in environments where volatile / explosive conditions could potentially exist. For storage of flammable or volatile materials within typical laboratory or non-volatile environments, see Flammable Material Storage units • Shipping weight: 240 lbs.