

SPEC SHEET CRT-ABT-HC-UCBI-0204

Product Name:	CRT-ABT-HC-UCBI-0204
Features:	<ul style="list-style-type: none"> • Undercounter Controlled Room Temperature Cabinet, Built-In • 2.5 Cu. Ft. Capacity • One solid swing door, right hinged • Microprocessor temperature controller • Digital temperature display • Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) • Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm • Audible and visual high and low temperature alarms • Remote alarm contacts • 2 probes; 1 in air and 1 in sample bottle • Four adjustable shelves (two large, two small) with guard rail on back to prevent product from being pushed against the back wall • Back wall evaporator cover • Vaccine storage power cord warning label • Forced draft circulation • Self-closing door • Keyed door lock • Magnetic door gasket for positive seal • Leveling legs • LED light • Probe access port (3/8") • Powder coat exterior • High density urethane foam cabinet and door insulation

SPEC SHEET CRT-ABT-HC-UCBI-0204

Product Name:	CRT-ABT-HC-UCBI-0204
Features:	<ul style="list-style-type: none"> • HFC-free refrigerant (R600a), foam insulation and packaging • Two year parts and labor warranty, plus an additional three year compressor parts only warranty • Pyxis®, Omnicell® and AcuDose RX® compatible • Exterior dimensions: 17 3/4" W x 22 3/4" D x 30 3/4" H • Cycle defrost • 115V, 60 Hz, .90 Amps, 1/8 HP • ADA compliant • UL/C-UL listed • Shipping weight: 85 lbs.