

SPEC SHEET CRT-ABT-HC-UCFS-0104

Product Name:	CRT-ABT-HC-UCFS-0104
Features:	<ul style="list-style-type: none"> • Undercounter Controlled Room Temperature Cabinet, Freestanding • 1 Cu. Ft. Capacity • One solid swing door, right hinged* • Microprocessor temperature controller • Digital temperature display • Audible and visual high and low temperature alarms • Remote alarm contacts • 2 probes; 1 in air and 1 in sample bottle • Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) • Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm • Back wall evaporator cover • 2 adjustable shelves • Vaccine storage power cord warning label • Forced draft circulation • Keyed door lock • Integrated door handle • Magnetic door gasket for positive seal • Leveling legs • LED interior light • Probe access port (3/8") • Powder coat exterior • High density urethane foam cabinet and door insulation

SPEC SHEET CRT-ABT-HC-UCFS-0104

Product Name:	CRT-ABT-HC-UCFS-0104
Features:	<ul style="list-style-type: none"> • HFC-free refrigerant (R600a), foam insulation and packaging • Two year parts and labor warranty, plus an additional three year compressor parts only warranty • Pyxis®, Omnicell® and AcuDose RX® compatible • Exterior dimensions: 17 ¼" W x 19 ¼" D x 21 ¼" H • Note: This unit must have 4" clearance on sides and back for adequate ventilation • Cycle defrost • 115V, 60 Hz, .90 Amps, 1/8 HP • UL/C-UL listed • Shipping weight: 91 lbs. • *This product is available left hinged, product number: CRT-ABT-HC-UCFS-0104-LH