

SPEC SHEET PH-ABT-HC-RFC12A

Product Name:	PH-ABT-HC-RFC12A
Features:	<ul style="list-style-type: none"> • Premier Pharmacy/Vaccine Refrigerator & Freezer Combination with Auto Defrost Freezer • 12 Cu. Ft. capacity (10.5 Ref./1.3 Freezer) • Two exterior solid swing doors (solid door refrigerator/solid door freezer), right hinged, not reversible • Microprocessor temperature controller, refrigerator and freezer • Digital temperature display, refrigerator and freezer • Adjustable operating temperature range: Refrigerator: 36°F – 46°F (2°C -8°C); Freezer: 5°F – -13°F (-15°C - -25°C) • Auto defrost cycle every 6 hours, max air temp in empty freezer: +4.34°C; max air temp in loaded freezer: -2.89°C. Max sample temp in empty freezer: -4.76°C; max sample temp in loaded freezer: - 9.58°C. • Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm • Audible and visual high and low temperature alarms, refrigerator and freezer • 2 probes; 1 in air and 1 in sample bottle, in both Refrigerator and Freezer • Remote alarm contacts, refrigerator and freezer • Six adjustable shelves with guard rail on back to prevent product from being pushed against back wall, Refrigerator • Two adjustable shelves with guard rail on back to prevent product from being pushed against back wall, Freezer • Bottom footed shelf to allow air circulation, Refrigerator and Freezer • Forced draft circulation, Refrigerator • Vaccine storage power cord warning label

SPEC SHEET PH-ABT-HC-RFC12A

Product Name:	PH-ABT-HC-RFC12A
Features:	<ul style="list-style-type: none"> • Keyed door locks • Magnetic door gasket for positive seal • Integrated door handles • Leveling legs • Stacking kit • Two probe access ports (3/8"); one, refrigerator/one, freezer • White powder coated exterior • HFC-free refrigerant (R600a), foam insulation and packaging • Pharmacy refrigerator/freezer toolkit and temperature logs • Two year parts and labor warranty, plus an additional three year compressor parts warranty • Exterior dimensions: 23 ¾" W x 26 ½" D x 80 ¼" H • Auto defrost freezer / cycle defrost refrigerator • 115V, 60 Hz, 2.3 Amps refrigerator, 1 Amp freezer, 1/3 HP refrigerator, 1/8 HP freezer • UL/C-UL listed • Shipping weight: 289 lbs. • *Please note this unit requires 2 outlets. • DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise the temperatures within the freezer.