

SPEC SHEET PH-ABT-HC-RFC7S

Product Name:	PH-ABT-HC-RFC7S
Features:	<ul style="list-style-type: none"> • Premier Pharmacy/Vaccine Refrigerator & Freezer Combination • 5.2 cu. ft. capacity (Refrigerator) / 1.7 cu. ft. capacity (Freezer) • Two exterior swing doors (solid door refrigerator/solid door freezer), right hinged, not reversible • Microprocessor temperature controller, refrigerator and freezer • Digital temperature display, refrigerator and freezer • Adjustable operating temperature range: Refrigerator: 36°F – 46°F (2°C -8°C); Freezer: 5°F – -13°F (-15°C - -25°C) • Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm • Audible and visual high and low temperature alarms, refrigerator and freezer • Remote alarm contacts, refrigerator and freezer • 2 probes; 1 in air and 1 in sample bottle, in both Refrigerator and Freezer • 3 adjustable shelves refrigerator/2 adjustable shelves freezer, shelves have back rails to prevent product from being pushed against back wall • Footed bottom shelf refrigerator, and freezer • Forced draft air circulation, refrigerator • Vaccine storage power cord warning label • Keyed door locks • Magnetic door gasket for positive seal • Integrated door handles • Leveling legs

SPEC SHEET PH-ABT-HC-RFC7S

Product Name:	PH-ABT-HC-RFC7S
Features:	<ul style="list-style-type: none"> • Stacking kit • Two probe access ports (3/8"); one, refrigerator/one, freezer • White powder coated exterior • HFC-free refrigerant (R600a), foam insulation and packaging • Pharmacy refrigerator/freezer toolkit and temperature logs • Two year parts and labor warranty, plus an additional three year compressor parts warranty • Exterior dimensions: 23 3/4" W x 24" D x 53 1/8" H • Manual defrost freezer / cycle defrost refrigerator • 115V, 60 Hz, 1.3 Amps refrigerator, 1 Amp freezer, 1/6 HP refrigerator, 1/8 HP freezer • UL/C-UL listed • Shipping weight: 215 lbs. • *Please note this unit requires 2 outlets.