

SPEC SHEET **ABT-HC-26-TS**

Product Name:	ABT-HC-26-TS
Features:	<ul style="list-style-type: none"> • TempLog Premier Glass Door Laboratory Refrigerator • 26 Cu. Ft. capacity • One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged • Microprocessor temperature controller • Adjustable operating temperature range: 1°C - 10°C • Touch Screen Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms • Password-protected control panel • Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit • Active temperature scale bar display • Resettable 1-point min/max history • Digital 24-hour temperature chart • Temperature data logging • USB port for data transfer and software updates • Real-time operational display clock • 4-20mA output • Electronic troubleshooting guide • Electronic QR Code to access Owner's Manual & technical support contact Information • Adjustable alarm volume • Audible and visual high/low temperature alarms • Sensor error alarm • Power failure alarm • Door ajar alarm • Low battery alarm

SPEC SHEET **ABT-HC-26-TS**

Product Name:	ABT-HC-26-TS
Features:	<ul style="list-style-type: none"> • Operation indicator • Alarm validation (audible, visual, and remote alarm) • Alarm mute with ring back • Remote alarm contacts • Four adjustable shelves (adjustable in ½" increments) • Forced draft air circulation • Keyed door lock • Magnetic door gasket for positive seal • Recessed door handle • LED interior lights are safety shielded and switch controlled • Swivel casters (adds 4" to height) • Probe access port (3/8") • White laminated vinyl exterior • White aluminum liner and stainless steel floor interior • HFC-free refrigerant (R290), foam insulation and packaging • Three year parts and labor warranty, plus an additional two year compressor parts warranty • Exterior dimensions: 30" W x 30 1/2" D x 82 5/8" H with casters; 78 5/8" H without casters • Cycle defrost • 115V, 60 Hz, 5.4 Amps, 1/3 HP, BTU/HR 4932 • UL/C-UL listed • ENERGY STAR CERTIFIED • Shipping weight: 345 lbs.