

**SPEC SHEET**    **ABT-HC-69-TS**

<b>Product Name:</b>	ABT-HC-69-TS
<b>Features:</b>	<ul style="list-style-type: none"> <li>• TempLog Premier Glass Door Laboratory Refrigerator</li> <li>• 69 Cu. Ft. capacity</li> <li>• Three sliding glass doors, self-closing (energy efficient, double pane vacuum insulated)</li> <li>• Microprocessor temperature controller</li> <li>• Adjustable operating temperature range: 1°C - 10°C</li> <li>• Touch Screen Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms</li> <li>• Password-protected control panel</li> <li>• Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit</li> <li>• Active temperature scale bar display</li> <li>• Resettable 1-point min/max history</li> <li>• Digital 24-hour temperature chart</li> <li>• Temperature data logging</li> <li>• USB port for data transfer and software updates</li> <li>• Real-time operational display clock</li> <li>• 4-20mA output</li> <li>• Electronic troubleshooting guide</li> <li>• Electronic QR Code to access Owner's Manual &amp; technical support contact Information</li> <li>• Adjustable alarm volume</li> <li>• Audible and visual high/low temperature alarms</li> <li>• Sensor error alarm</li> <li>• Power failure alarm</li> <li>• Door ajar alarm</li> </ul>

**SPEC SHEET**    **ABT-HC-69-TS**

<b>Product Name:</b>	ABT-HC-69-TS
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Low battery alarm</li> <li>• Operation indicator</li> <li>• Alarm validation (audible, visual, and remote alarm)</li> <li>• Alarm mute with ring back</li> <li>• Remote alarm contacts</li> <li>• Twelve adjustable shelves (adjustable in ½" increments)</li> <li>• Forced draft air circulation</li> <li>• Keyed door lock</li> <li>• Magnetic door gasket for positive seal</li> <li>• Integrated door handles</li> <li>• LED interior lights are safety shielded and switch controlled</li> <li>• Swivel casters (adds 4" to height)</li> <li>• Probe access port (3/8")</li> <li>• White laminated vinyl exterior</li> <li>• White aluminum liner and stainless steel floor interior</li> <li>• HFC-free refrigerant (R290), foam insulation and packaging</li> <li>• Three year parts and labor warranty, plus an additional two year compressor parts warranty</li> <li>• Exterior dimensions: 78 ¼"W x 30 ¾"D x 82 5/8" H with casters; 78 5/8" H without casters</li> <li>• Cycle defrost</li> <li>• 115V, 60 Hz, 9.3 Amps, 1/2 HP, BTU/HR 7315</li> <li>• UL/C-UL listed</li> <li>• Shipping weight: 695 lbs.</li> </ul>