

**SPEC SHEET CRT-ABT-HC-10PS**

<b>Product Name:</b>	CRT-ABT-HC-10PS
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Upright Controlled Room Temperature Cabinet, Solid Door</li> <li>• 10.5 Cu. Ft. Capacity</li> <li>• One solid swing door, right hinged, not reversible</li> <li>• Microprocessor temperature controller</li> <li>• Digital temperature display</li> <li>• Audible and visual high and low temperature alarms</li> <li>• 2 probes; 1 in air and 1 in sample bottle</li> <li>• Remote alarm contacts</li> <li>• Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)</li> <li>• Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual &amp; audible temp alarm</li> <li>• Six adjustable shelves with guard rail on back to prevent product from being pushed against back wall</li> <li>• Bottom footed shelf to allow air circulation</li> <li>• Back wall evaporator cover</li> <li>• Vaccine storage power cord warning label</li> <li>• Forced draft circulation</li> <li>• Keyed door lock</li> <li>• Magnetic door gasket for positive seal</li> <li>• Leveling legs</li> <li>• LED interior light</li> <li>• Probe access port (3/8")</li> <li>• Powder coat exterior</li> </ul>

**SPEC SHEET CRT-ABT-HC-10PS**

<b>Product Name:</b>	CRT-ABT-HC-10PS
<b>Features:</b>	<ul style="list-style-type: none"> <li>• High density urethane foam cabinet insulation</li> <li>• HFC-free refrigerant (R600a), foam insulation and packaging</li> <li>• Vaccine toolkit and temperature logs</li> <li>• Two year parts and labor warranty, plus an additional three year compressor parts warranty</li> <li>• Pyxis®, Omnicell® and AcuDose RX® compatible</li> <li>• Exterior dimensions: 23 ¾" W x 26 ½" D x 59" H</li> <li>• Note: This unit must have 4" clearance on sides and back for adequate ventilation</li> <li>• UL/C-UL listed</li> <li>• Cycle defrost</li> <li>• 115V, 60 Hz, 1/3 HP, 2.3 Amps</li> <li>• Shipping weight: 183 lbs.</li> </ul>